Model No. 3399F





Drain/pipe Inspection Camera System with 40m(or 50m, 60m) cable

Camera Head:

- ♦ Material: #304 Stainless Steel
- Sensor: 1/3" Sony CCD, 480 TV Lines
- View Angle: 120°
- Focal Distance: 12-120cm
- Two Roller Skids, Mini one at dia.72mm, another universal skid at dia. 115-250mm
- LEDs: 12pcs high light LEDs
- Waterproof: Max. 20m under water
- Built-in 512Hz Sonde (optional)
- With self-leveling feature

- Cable dia. 6.8 mm

Monitor:

- 7" LCD color TFT LCD
- With universal installation brackets
- ◆ SD Card slot to store still pictures or videos
- One push record button
- ♦ Built-in rechargeable battery lasts up to 5 hours
- On-Screen date and time
- On-screen meter/ft. distance display



















Mini Roller Skid, (Dia. 70mm) for pipe dia. 75mm-120mm



Universal Roller Skid, dia. 120mm(Min.) 250mm(Max.) for pipe dia. 125mm- 300mm



Stand Horizontally

Universal bracket to install monitor on top or side of the wheel







Specifications

Camera Head

Material: #304 Stainless Steel Dimension: ¢ 38mm×81mm(Main body) Sensor: 1/3" Sony CCD, 480 TV Lines

View Angle: 120° Focal Distance: 12-120cm Two Roller Skids, Mini one at dia.72mm, another universal skid at dia. 115-250mm

Saphire glass for scratch proof

LEDs: 12pcs high light LEDs Waterproof: Max. 20m under water

Built-in 512Hz Sonde (optional) With self-leveling

Push Cable

Cable dia. 6.8 mm Cable Material: Fiberglass Available length: 40/50/60m Wheel material: Stainless steel

7" 16:9 high definition color LCD monitor One push record button Resolution: 800*480 R.G.B. Built-in rechargeable battery Encoding: H.264 Work time: 4-5 hours With universal installation bracket Charge time: 6-7 hours SD Card slot to store still images or videos On-Screen date and time Local audio recording On-screen meter/ft. distance display Menu Language: English, German, French, Spanish, Italian, Chinese, Japanese, Russian, Portuguese